



DMX Protocol Map

MOSAIC-4x4, MOSAIC-3x6, MOSAIC 2x4, MOSAIC TUBE, ALL-IN COLOR

Simple CCT Crossfade RGBW (8 Channels)

DMX Channel	Value	Percent	Function
1	0 - 255	0 - 100	Dimmer 0 - 100%
2	0 - 255	0 - 100	Color Temperature 2'200K - 12000K
3	0 - 10		Neutral, No Effect
	11 - 20		Full MINUS Green
	21 - 119		-99% - 1%
	120 - 145		Neutral, No Effect
	146 - 244		1% - 99%
	245 - 255		Full PLUS Green
4	0 - 255	0 - 100	Crossfade 0 - 100%
5	0 - 255	0 - 100	Intensity Red 0 - 100%
6	0 - 255	0 - 100	Intensity Green 0 - 100%
7	0 - 255	0 - 100	Intensity Blue 0 - 100%
8	0 - 255	0 - 100	Intensity White 0 - 100%

Expert CCT Crossfade RGBW + Effects (11 Channels)

DMX Channel	Value	Percent	Function
1	0 - 255	0 - 100	Dimmer 0 - 100%
2	0 - 255	0 - 100	Color Temperature 2'200K - 12000K
3	0 - 10		Neutral, No Effect
	11 - 20		Full MINUS Green
	21 - 119		-99% - 1%
	120 - 145		Neutral, No Effect
	146 - 244		1% - 99%

3	245 - 255		Full PLUS Green
4	0 - 255	0 - 100	Crossfade 0 - 100%
5	0 - 255	0 - 100	Intensity Red 0 - 100%
6	0 - 255	0 - 100	Intensity Green 0 - 100%
7	0 - 255	0 - 100	Intensity Blue 0 - 100%
8	0 - 255	0 - 100	Intensity White 0 - 100%
9	0 - 9		No Effect
	10 - 19		1. Strobe
	20 - 29		2. Fade
	30 - 39		3. Flicker
	40 - 49		4. Flash
	50 - 59		5. Police
	60 - 69		6. Welding
	70 - 79		7. Fire
	80 - 89		8. Candle
	90 - 99		9. Television
	100 - 109		10. Dissolve
110 - 255		No Effect	
10	0 - 255	0 - 100	Dimming (FX) 0 - 100%
11	0 - 255	0 - 100	Speed (FX) 0 - 100%

DMX Protocol Map

ALL-IN-LINE

DMX Channel	Value	Percent	Function
1	0 - 255	0 - 100	Dimmer Closed – Open
2	0 - 255	0 - 100	Color Temperature CCT 2900K – 6300K
3	0 - 255	0 - 100	Intensity Red 0 - 100%
4	0 - 255	0 - 100	Intensity Green 0 - 100%
5	0 - 255	0 - 100	Intensity Blue 0 - 100%



DMX Protocol Map

ALL-IN 1 Bi-Color, ALL-IN 2 Bi-Color, ALL-WHIP, ALL-CAPE

DMX Channel	Value	Percent	Function
1	0 - 255	0 - 100	Dimmer Closed – Open
2	0 - 255	0 - 100	Color Temperature CCT 2900K – 6300K

DMX Protocol Map

BI-FABRIC 2, BI-FABRIC 4

DMX Channel	Value	Percent	Function
1	0 - 255	0 - 100	Dimmer Closed – Open
2	0 - 255	0 - 100	Color Temperature CCT 2900K – 6000K



DMX Protocol Map

FABRIC-LITE 20, FABRIC-LITE 35

DMX Channel	Value	Percent	Function
1	0 - 255	0 - 100	Dimmer Closed – Open
2	0 - 255	0 - 100	Color Temperature CCT 2900K – 6000K



DMX Protocol Map

BI-FLEX M7, BI-FLEX M3

DMX Channel	Value	Percent	Function
1	0 - 255	0 - 100	Dimmer Closed – Open
2	0 - 255	0 - 100	Color Temperature CCT 2900K – 5600K



DMX Protocol Map

BASE-LITE 100, BASE-LITE 200

DMX Channel	Value	Percent	Function
1	0 - 255	0 - 100	Dimmer Closed – Open
2	0 - 255	0 - 100	Color Temperature CCT 2900K – 6400K